# Move/2500

Guarantee terminal's availability whatever happens





### Highest security

The Move/2500 is PCI-PTS 5.x certified. Its Telium TETRA OS uses the latest cryptographic schemes with future-proof key length.

## All payment options

The Move/2500 enables NFC couponing and wallet use cases, in addition to EMV Chip & PIN, swipe and contactlesss.

# Designed for mobility

Designed for indoor and outdoor use, the Move/2500 Portable is a pocket-size and offers extended battery. It is the perfect business companion for merchants.

## Guaranteed terminal availability

In a single terminal, the Move/2500 Hybrid comes with wired communication capabilities (Ethernet, PSTN) or wireless (4G,3G, GPRS, Dual SIM) or WiFi. Then it guarantees terminal payment acceptance availability in case of network failures.





## Seamless NFC payment

The Move/2500 boosts contactless payment by offering customers a seamless experience through a dedicated card-reader zone and faster transaction flow.



# Secure Telium TETRA OS

Backed by 40 years of experience and with its user-friendly interface, the Telium TETRA operating system includes the best security mechanisms embedded to protect transaction privacy and leverages Ingenico's unique portfolio of payment applications.

## Compatible with Ingenico's suite of services

Keeping the solutions connected, the Move/2500 works in unison with Ingenico's supporting service platforms, meaning merchants will have access to business services such as back office reporting and e-receipt management. Software updates and day-to-day support deliver a hassle-free experience.

The Move/2500 is supported by our Cloud Service



			MOVE/ 2500 HYBRID	MOVE/ 2500 PORT.
Processor	Application     & Crypto processor	• Cortex A5	•	•
Memory		• 256 MB Flash, 128 MB RAM • 512 MB Flash, 128 MB RAM	• Option	• Option
OS		• Telium TETRA	•	•
SIM		• 2 SIM	Option	Option
SAM		• 2 SAM • 3rd SAM	• Option	• Option
Card readers	Magstripe     Smart card     NFC/Contactless	• ISO 1/2/3, 500K lifespan • EMV Level 1, 500K lifespan • EMV Level 1 compliant	•	•
Display	• Colour	• 2.4" backlit, QVGA (320x240 pixels)	•	•
Keypad		16 keys, raised marking, backlit     4 Functional Keys without backlight	•	•
Audio	• Buzzer		•	•

Thermal Printer	Speed in lines/s     Paper roll cage	• up to 24 lines/s • 58 mm width x Ø 40 mm	•	•
Terminal connectivity	• WAN • LAN • Wired	4G* (fallback GPRS only) or/ and 3G and/or GPRS     WiFi     Dial-up Modem RJ45     Ethernet 10/100 base T RJ45	Option Option	Option Option N/A N/A
Terminal connections	USB Serial Power Supply	Micro USB Host & Slave     RS 232 RJ11     Dedicated power jack	•	N/A
Battery	• Li-ion	• 2200mAh	•	•
Terminal size	Portable     Hybrid	• 168x81x58 mm (6.6x3.2x2.3") • 168x81x69 mm (6.6x3.2x2.7")	N/A	N/A
Weight	• Terminal + Battery	• 320 g (11 oz)	•	•
Environment	Operating Temperature     Storage     Temperature     Operating     Humidity	10°C to +40°C (14°F to 104°F) - 20°C to +55°C (-4°F to 131°F) - 85% non-condensing at +40°C (104°F)	•	•
Security		• PCI PTS 5.x & 4.x online & offline certified	•	•

\*Depending countries





MOVE/

2500 PORT.